

Safety Data Sheet

according to Regulation (EC) No 1907/2006

FAM

Print date: 01.12.2015

Product code:

Page 1 of 15

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

FAM

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Industrial use resulting in manufacture of another substance (use of intermediates)

Uses advised against

any non-intended use.

1.3. Details of the supplier of the safety data sheet

Company name:	Thierry GmbH	
Street:	Motorstrasse 30	
Place:	D-70499 Stuttgart	
Telephone:	+49 (0)711 8399 7470	Telefax: +49 (0)711 8399 7480
e-mail:	info@thierry-gmbh.de	
Contact person:	Veronika Krieger	Telephone: 0711/839974-0
Internet:	www.thierry-gmbh.de	
Responsible Department:	Dr. Gans-Eichler	e-mail: info@tge-consult.de
	Chemieberatung GmbH	Tel.: +49 (0)251/924520-60
	Raesfeldstr. 22	www.tge-consult.de
	D-48149 Münster	

1.4. Emergency telephone number:

Emergency medical information: Poison Information Center Mainz - Tel: +49 (6131) 19240

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Regulation (EC) No. 1272/2008**

Hazard categories:

Flammable liquid: Flam. Liq. 2

Skin corrosion/irritation: Skin Irrit. 2

Reproductive toxicity: Repr. 2

Specific target organ toxicity - single exposure: STOT SE 3

Specific target organ toxicity - repeated exposure: STOT RE 2

Aspiration hazard: Asp. Tox. 1

Hazardous to the aquatic environment: Aquatic Acute 1

Hazardous to the aquatic environment: Aquatic Chronic 1

Hazard Statements:

Highly flammable liquid and vapour.

May be fatal if swallowed and enters airways.

Causes skin irritation.

May cause drowsiness or dizziness.

Suspected of damaging the unborn child.

May cause damage to organs through prolonged or repeated exposure.

Very toxic to aquatic life with long lasting effects.

2.2. Label elements**Regulation (EC) No. 1272/2008****Hazard components for labelling**

toluene

octane; 2,2,4-trimethylpentane

2,4,4-trimethylpent-2-ene

Safety Data Sheet

according to Regulation (EC) No 1907/2006

FAM

Print date: 01.12.2015

Product code:

Page 2 of 15

Signal word: Danger**Pictograms:****Hazard statements**

H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H410	Very toxic to aquatic life with long lasting effects.

Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260	Do not breathe vapour/aerosol.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P331	Do NOT induce vomiting.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.

2.3. Other hazards

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.
In use, may form flammable/explosive vapour-air mixture.

SECTION 3: Composition/information on ingredients**3.2. Mixtures**

Safety Data Sheet

according to Regulation (EC) No 1907/2006

FAM

Print date: 01.12.2015

Product code:

Page 3 of 15

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification according to Regulation (EC) No. 1272/2008 [CLP]			
108-88-3	toluene			50 - < 55 %
	203-625-9	601-021-00-3		
	Flam. Liq. 2, Repr. 2, Skin Irrit. 2, STOT SE 3, STOT RE 2, Asp. Tox. 1; H225 H361d H315 H336 H373 H304			
540-84-1	octane; 2,2,4-trimethylpentane			30 - < 35 %
	208-759-1	601-009-00-8		
	Flam. Liq. 2, Asp. Tox. 1, Skin Irrit. 2, STOT SE 3, Aquatic Acute 1, Aquatic Chronic 1; H225 H304 H315 H336 H400 H410			
107-39-1	2,4,4-trimethylpent-1-ene			15 - < 20 %
	203-486-4	601-031-00-8		
	Flam. Liq. 2, Aquatic Chronic 2; H225 H411			
107-40-4	2,4,4-trimethylpent-2-ene			5 - < 10 %
	203-488-5			
	Flam. Liq. 2, Skin Irrit. 2, Eye Irrit. 2, STOT SE 3, Asp. Tox. 1; H225 H315 H319 H335 H304			
64-17-5	ethanol, ethyl alcohol			5 - < 10 %
	200-578-6	603-002-00-5	01-2119457610-43	
	Flam. Liq. 2, Eye Irrit. 2; H225 H319			

Full text of H and EUH statements: see section 16.

Further Information

Product does not contain listed SVHC substances > 0,1 % according to Regulation (EC) No. 1907/2006 Article 59 (REACH)

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Take off immediately all contaminated clothing.

After inhalation

In case of accident by inhalation: remove casualty to fresh air and keep at rest. If breathing is irregular or stopped, administer artificial respiration. If experiencing respiratory symptoms: Call a doctor.

After contact with skin

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. If skin irritation or rash occurs: Get medical advice/attention.

After contact with eyes

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. In case of eye irritation consult an ophthalmologist.

After ingestion

Rinse mouth thoroughly with water. Let water be drunken in little sips (dilution effect). Do NOT induce vomiting. Never give anything by mouth to an unconscious person or a person with cramps. When in doubt or if symptoms are observed, get medical advice.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

FAM

Print date: 01.12.2015

Product code:

Page 4 of 15

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**alcohol resistant foam. dry extinguishing powder. Carbon dioxide (CO₂).**Unsuitable extinguishing media**

High power water jet.

5.2. Special hazards arising from the substance or mixtureCan be released in case of fire: Carbon monoxide. Carbon dioxide (CO₂).**5.3. Advice for firefighters**

In case of fire and/or explosion do not breathe fumes. Wear a self-contained breathing apparatus and chemical protective clothing.

Additional information

Use water spray jet to protect personnel and to cool endangered containers.

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Remove persons to safety. Provide adequate ventilation. Remove all sources of ignition.

Do not breathe vapour/aerosol. Avoid contact with skin, eyes and clothes.

Wear personal protection equipment (refer to section 8).

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Discharge into the environment must be avoided. Prevent spread over a wide area (e.g. by containment or oil barriers). In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).

Treat the recovered material as prescribed in the section on waste disposal.

Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

Provide adequate ventilation.

Wear suitable protective clothing. (See section 8.)

Avoid contact with skin, eyes and clothes.

Do not breathe vapour/aerosol.

Advice on protection against fire and explosion

Keep away from sources of ignition. - No smoking. Take precautionary measures against static discharges.

Heating causes rise in pressure with risk of bursting.

Further information on handling

Flammable vapours can accumulate in head space of closed systems.

General protection and hygiene measures: refer to chapter 8

Safety Data Sheet

according to Regulation (EC) No 1907/2006

FAM

Print date: 01.12.2015

Product code:

Page 5 of 15

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep container tightly closed in a cool, well-ventilated place. Keep container dry.

Make sure spills can be contained (e.g. sump pallets or kerbed areas).

Ensure adequate ventilation of the storage area.

Advice on storage compatibility

Do not store together with: Gas. Explosives. Flammable solids. Pyrophoric liquids and solids. Self-heating substances and mixtures. Substances and mixtures which, in contact with water, emit flammable gases.

Oxidizing liquids. Oxidizing solids. ammonium nitrate. Self-reactive substances and mixtures. Organic peroxides. Non-combustible toxic substances. Radioactive substances. Infectious substances.

Further information on storage conditions

Protect against: Light. UV-radiation/sunlight. heat. Cold moisture.

7.3. Specific end use(s)

refer to section 1.

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
64-17-5	Ethanol	1000	1920		TWA (8 h)	WEL
		-	-		STEL (15 min)	WEL
108-88-3	Toluene	50	191		TWA (8 h)	WEL
		100	384		STEL (15 min)	WEL

Safety Data Sheet

according to Regulation (EC) No 1907/2006

FAM

Print date: 01.12.2015

Product code:

Page 6 of 15

DNEL/DMEL values

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
108-88-3	toluene			
Worker DNEL, acute		inhalation	local	384 mg/m³
Consumer DNEL, acute		inhalation	systemic	226 mg/m³
Worker DNEL, long-term		inhalation	local	192 mg/m³
Worker DNEL, long-term		inhalation	systemic	192 mg/m³
Worker DNEL, long-term		dermal	systemic	384 mg/kg bw/day
Consumer DNEL, acute		inhalation	local	226 mg/m³
Consumer DNEL, long-term		inhalation	systemic	56,5 mg/m³
Consumer DNEL, long-term		dermal	systemic	226 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	8,13 mg/kg bw/day
64-17-5	ethanol, ethyl alcohol			
Worker DNEL, acute		inhalation	local	1900 mg/m³
Worker DNEL, long-term		dermal	systemic	343 mg/kg bw/day
Worker DNEL, long-term		inhalation	systemic	950 mg/m³
Consumer DNEL, acute		inhalation	local	950 mg/m³
Consumer DNEL, long-term		dermal	systemic	206 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	114 mg/m³
Consumer DNEL, long-term		oral	systemic	87 mg/kg bw/day

PNEC values

CAS No	Substance		
Environmental compartment			Value
108-88-3	toluene		
Freshwater			0,68 mg/l
Freshwater sediment			16,39 mg/kg
Micro-organisms in sewage treatment plants (STP)			13,61 mg/l
Soil			2,89 mg/kg
64-17-5	ethanol, ethyl alcohol		
Freshwater			0,96 mg/l
Freshwater (intermittent releases)			2,75 mg/l
Marine water			0,79 mg/l
Marine water (intermittent releases)			2,75 mg/l
Freshwater sediment			3,6 mg/kg
Secondary poisoning			720 mg/kg
Micro-organisms in sewage treatment plants (STP)			580 mg/l
Soil			0,63 mg/kg

8.2. Exposure controls

Safety Data Sheet

according to Regulation (EC) No 1907/2006

FAM

Print date: 01.12.2015

Product code:

Page 7 of 15



Appropriate engineering controls

Provide adequate ventilation as well as local exhaust at critical locations.

Protective and hygiene measures

Always close containers tightly after the removal of product. When using do not eat, drink, smoke, sniff. Wash hands before breaks and after work. Remove contaminated clothing immediately and dispose off safely.

Eye/face protection

Eye glasses with side protection

Hand protection

In case of prolonged or frequently repeated skin contact: Wear suitable gloves.

Suitable material:

(penetration time (maximum wearing period): ≥ 8 Stunden):

FKM (fluororubber).

Before using check leak tightness / impermeability. In the case of wanting to use the gloves again, clean them before taking off and air them well.

The selected protective gloves have to satisfy the specifications of EU Directive 89/686/EEC and the standard EN 374 derived from it.

Skin protection

Wear fire/flame resistant/retardant clothing.

Minimum standard for preventive measures while handling with working materials are specified in the TRGS 500.

Respiratory protection

Respiratory protection necessary at:

exceeding exposure limit values

insufficient ventilation

Suitable respiratory protective equipment:

gas filtering equipment (EN 141). Type: A

The filter class must be suitable for the maximum contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If the concentration is exceeded, closed-circuit breathing apparatus must be used!

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	liquid
Colour:	colourless
Odour:	characteristic

Test method

pH-Value:	not determined
-----------	----------------

Changes in the physical state

Melting point:	not determined
Initial boiling point and boiling range:	not determined
Pour point:	not determined
Flash point:	< 6 °C

Safety Data Sheet

according to Regulation (EC) No 1907/2006

FAM

Print date: 01.12.2015

Product code:

Page 8 of 15

Explosive properties

In use, may form flammable/explosive vapour-air mixture.

Lower explosion limits: not determined

Upper explosion limits: not determined

Ignition temperature: not determined

Oxidizing properties

none

Vapour pressure: not determined

Density: not determined

Water solubility: not determined

Viscosity / dynamic: not determined

Viscosity / kinematic: not determined

Solvent content: not determined

9.2. Other information

Solid content: not determined

SECTION 10: Stability and reactivity**10.1. Reactivity**

No information available.

10.2. Chemical stability

The product is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

No information available.

10.4. Conditions to avoid

Protect against: Light. UV-radiation/sunlight. heat. Cold. moisture.

10.5. Incompatible materials

Materials to avoid: Strong acid. strong alkalis. Oxidizing agents, strong. Peroxides. Reducing agents, strong.

10.6. Hazardous decomposition productsCan be released in case of fire: Carbon monoxide. Carbon dioxide (CO₂).**SECTION 11: Toxicological information****11.1. Information on toxicological effects****Toxicokinetics, metabolism and distribution**

No information available.

Acute toxicity

Based on available data, the classification criteria are not met.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

FAM

Print date: 01.12.2015

Product code:

Page 9 of 15

CAS No	Chemical name				
	Exposure routes	Method	Dose	Species	Source
108-88-3	toluene				
	oral	LD50	>5000 mg/kg	Rat	ECHA Dossier
	dermal	LD50	>5000 mg/kg	Rabbit	ECHA Dossier
	inhalative (4 h) vapour	LC50	28,1 mg/l	Rat	ECHA Dossier
540-84-1	octane; 2,2,4-trimethylpentane				
	oral	LD50	>5000 mg/kg	Rat	ECHA Dossier
	dermal	LD50	>2000 mg/kg	Rabbit	ECHA Dossier
	inhalative (4 h) aerosol	LC50	>33,52 mg/l	Rat	ECHA Dossier
64-17-5	ethanol, ethyl alcohol				
	oral	LD50	>5000 mg/kg	Rat.	ECHA Dossier
	inhalative (4 h) vapour	LC50	51-124,7 mg/l	Rat.	ECHA Dossier

Irritation and corrosivity

Causes skin irritation.

Sensitising effects

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (toluene), (octane; 2,2,4-trimethylpentane)

Severe effects after repeated or prolonged exposure

May cause damage to organs through prolonged or repeated exposure. (toluene)

toluene (CAS-No.: 108-88-3):

Subchronic oral toxicity

Exposure time: 13 weeks

Species: Mouse.

Method: OECD Guideline 408

Result: NOAEL = 625 mg/kg bw/day

literature information: ECHA Dossier

Ethanol. (CAS-No.: 64-17-5):

Subchronic oral toxicity

Exposure time: 90d

Species: Sprague-Dawley Rat.

Method: OECD Guideline 408

Result: NOAEL = 1280 mg/kg

literature information: ECHA Dossier

Carcinogenic/mutagenic/toxic effects for reproduction

Safety Data Sheet

according to Regulation (EC) No 1907/2006

FAM

Print date: 01.12.2015

Product code:

Page 10 of 15

Suspected of damaging the unborn child. (toluene)
toluene (CAS-No.: 108-88-3):
In-vitro mutagenicity: No experimental indications of mutagenicity in-vitro exist.
Reproductive toxicity:
Exposure time: 95d
Species: Rat
Method: OECD Guideline 416
Result: NOAEC = 500 ppm
Developmental toxicity/teratogenicity:
Exposure time: 20d
Species: Rat.
Method: EPA OTS 798.4350 (Inhalation Developmental Toxicity Screen)
Result: NOAEC = 750 ppm (maternal toxicity)
Result: NOAEC = 750 ppm (developmental toxicity)
literature information: ECHA Dossier

Ethanol. (CAS-No.: 64-17-5):
In-vitro mutagenicity: No experimental indications of mutagenicity in-vitro exist.
Reproductive toxicity:
Exposure time: 18 weeks
Species: CD-1 Mouse.
Method: OECD Guideline 416
Result: NOAEL = 20700 mg/kg/day
Developmental toxicity/teratogenicity:
Exposure time: 19d
Species: Sprague-Dawley Rat.
Method: OECD Guideline 414
Result: NOAEL = 16000 ppm (maternal toxicity)
Result: NOAEL >= 20000 ppm (teratogenicity)
literature information: ECHA Dossier

octane; 2,2,4-trimethylpentane (CAS-No.: 540-84-1):
In-vitro mutagenicity: No experimental indications of mutagenicity in-vitro exist.
literature information: ECHA Dossier

Aspiration hazard

May be fatal if swallowed and enters airways.

Specific effects in experiment on an animal

No information available.

SECTION 12: Ecological information**12.1. Toxicity**

Safety Data Sheet

according to Regulation (EC) No 1907/2006

FAM

Print date: 01.12.2015

Product code:

Page 11 of 15

CAS No	Chemical name					
	Aquatic toxicity	Method	Dose	[h] [d]	Species	Source
108-88-3	toluene					
	Acute fish toxicity	LC50	(5,5) mg/l	96 h	Oncorhynchus kisutch	ECHA Dossier
	Acute crustacea toxicity	EC50	(3,78) mg/l	48 h	Ceriodaphnia dubia	ECHA Dossier
	Acute bacteria toxicity		(134 mg/l)	3 h	Chlorella vulgaris and Chlamydomonas angulosa	ECHA Dossier
64-17-5	ethanol, ethyl alcohol					
	Acute fish toxicity	LC50	14200 mg/l	96 h	Pimephales promelas	ECHA Dossier
	Acute algae toxicity	ErC50	275 mg/l	72 h	Chlorella vulgaris	ECHA Dossier
	Acute crustacea toxicity	EC50	5012 mg/l	48 h	Ceriodaphnia dubia	ECHA Dossier
	Crustacea toxicity	NOEC	9,6 mg/l	9 d	Daphnia magna	ECHA Dossier

12.2. Persistence and degradability

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
64-17-5	ethanol, ethyl alcohol			
	other guideline	84%	20	ECHA Dossier
	Product is biodegradable.			

12.3. Bioaccumulative potential**Partition coefficient n-octanol/water**

CAS No	Chemical name	Log Pow
108-88-3	toluene	2,73
64-17-5	ethanol, ethyl alcohol	-0,31

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects

No information available.

Further information

Do not allow uncontrolled discharge of product into the environment.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Advice on disposal**

Dispose of waste according to applicable legislation. Consult the appropriate local waste disposal expert about waste disposal. Non-contaminated packages may be recycled. According to EAKV, allocation of waste identity numbers/waste descriptions must be carried out in a specific way for every industry and process.

Control report for waste code/ waste marking according to EAKV:

Waste disposal number of waste from residues/unused products

160305 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; off-specification batches and unused products; organic wastes containing hazardous substances
Classified as hazardous waste.

Waste disposal number of used product

Safety Data Sheet

according to Regulation (EC) No 1907/2006

FAM

Print date: 01.12.2015

Product code:

Page 12 of 15

160305 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; off-specification batches and unused products; organic wastes containing hazardous substances
Classified as hazardous waste.

Waste disposal number of contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances
Classified as hazardous waste.

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number: UN 1993
14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S.
 (toluene; octane; 2,2,4-trimethylpentane)
14.3. Transport hazard class(es): 3
14.4. Packing group: II
 Hazard label: 3



Classification code: F1
 Special Provisions: 274 601 640C
 Limited quantity: 1 L
 Excepted quantity: E2
 Transport category: 2
 Hazard No: 33
 Tunnel restriction code: D/E

Inland waterways transport (ADN)

14.1. UN number: UN 1993
14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S.
 (toluene; octane; 2,2,4-trimethylpentane)
14.3. Transport hazard class(es): 3
14.4. Packing group: II
 Hazard label: 3



Classification code: F1
 Special Provisions: 274 601 640C
 Limited quantity: 1 L
 Excepted quantity: E2

Marine transport (IMDG)

14.1. UN number: UN 1993
14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S.
 (toluene; 2,2,4-trimethylpentane)
14.3. Transport hazard class(es): 3

Safety Data Sheet

according to Regulation (EC) No 1907/2006

FAM

Print date: 01.12.2015

Product code:

Page 13 of 15

14.4. Packing group:

II

Hazard label:

3



Marine pollutant:

YES

Special Provisions:

274

Limited quantity:

1 L

Excepted quantity:

E2

EmS:

F-E, S-E

Air transport (ICAO)**14.1. UN number:**

UN 1993

14.2. UN proper shipping name:FLAMMABLE LIQUID, N.O.S.
(toluene; 2,2,4-trimethylpentane)**14.3. Transport hazard class(es):**

3

14.4. Packing group:

II

Hazard label:

3



Special Provisions:

A3

Limited quantity Passenger:

1 L

Passenger LQ:

Y341

Excepted quantity:

E2

IATA-packing instructions - Passenger:

353

IATA-max. quantity - Passenger:

5 L

IATA-packing instructions - Cargo:

364

IATA-max. quantity - Cargo:

60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS:

yes



Danger releasing substance:

octane; 2,2,4-trimethylpentane

14.6. Special precautions for user

See section 8.

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

not relevant.

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

2010/75/EU (VOC):

not determined

2004/42/EC (VOC):

not determined

Information according to 2012/18/EU
(SEVESO III):

E1 Hazardous to the Aquatic Environment

Additional information:

Additional information

Safety Data Sheet

according to Regulation (EC) No 1907/2006

FAM

Print date: 01.12.2015

Product code:

Page 14 of 15

This mixture is classified as hazardous according to regulation (EC) No. 1272/2008 [CLP].
REACH 1907/2006 Appendix XVII, No 3

National regulatory information

Employment restrictions: Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water contaminating class (D): 2 - water contaminating

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Changes

Rev. 1.00; 25.11.2015, Initial release

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route
CAS Chemical Abstracts Service
DNEL: Derived No Effect Level
IARC: INTERNATIONAL AGENCY FOR RESEARCH ON CANCER
International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)
ICAO: International Civil Aviation Organization
ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)
GHS: Globally Harmonized System of Classification and Labelling of Chemicals
GefStoffV: Gefahrstoffverordnung (Ordinance on Hazardous Substances, Germany)
LOAEL: Lowest observed adverse effect level
LOAEC: Lowest observed adverse effect concentration
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
NOAEL: No observed adverse effect level
NOAEC: No observed adverse effect level
NTP: National Toxicology Program
N/A: not applicable
OSHA: Concerning the International Transport of Dangerous Goods by Rail)
PNEC: predicted no effect concentration
PBT: Persistent bioaccumulative toxic
RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
SARA: Superfund Amendments and Reauthorization Act
SVHC: substance of very high concern
TRGS Technische Regeln für Gefahrstoffe
TSCA: Toxic Substances Control Act
VOC: Volatile Organic Compounds
VwVwS: Verwaltungsvorschrift wassergefährdender Stoffe
WGK: Wassergefährdungsklasse

Relevant H and EUH statements (number and full text)

H225 Highly flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H319 Causes serious eye irritation.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

FAM

Print date: 01.12.2015

Product code:

Page 15 of 15

H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)